



Marine Rescue Technologies Ltd, Wescom Group Unit J1, Springfield Way, Anlaby, HU10 6RJ, United Kingdom
+44 (0)1482 679300 | smrt@wescom-group.com | www.smrtsos.com

SERVICE BULLETIN

Issue Number: MRT-001

Published: 17th February 2026

sMRT SARfinder installation and operational compliance

Product Affected: sMRT SARfinder

The sMRT SARfinder must be installed in a location protected from direct exposure to water and from any risk of water ingress.

As the unit is not waterproof and is not designed for installation in exposed or external environments, any water ingress may adversely affect performance, reliability, and long-term operation, and may result in malfunction.

Please note, no action is required if your sMRT SARfinder is already installed and operated in a suitable location.

Operational Instructions

Customers are also reminded to, where possible, ensure that the correct start-up and shutdown procedures are followed.

To correctly turn the device off:

- Press the **[POWER]** button located on the front right hand side of the unit.
- This will display a **[POWER OFF]** icon on the main screen.
- Touch the **[POWER OFF]** icon on the screen to switch the SARfinder off.



Recommended Testing Procedure

The sMRT SARfinder forms part of the vessel's safety system and should be included in your regular testing regime. Testing should be carried out in accordance with the user manual, the latest version of which is available on the smrtsos.com website.

Should you have any questions, encounter any issues or require technical support, please contact the Customer Service team at: mrtcustmerservice@wescom-group.com.