

sMRT V300

The sMRT V300 is an advanced, commercial grade, man overboard (MOB) device incorporating AIS, VHF DSC, and 121.5 MHz technologies. It features water activation technology, audible and visual indicators, and offers multiple fixing options for life jacket integration.

With an increased signalling range and Class M compliance, the sMRT V300 ensures accelerated alerting and reliable location tracking over extended distances. This results in improved effectiveness and efficiency of rescue efforts during a man overboard incident.



VHF DSC

VHF DSC

All nearby vessels are automatically alerted of the man overboard situation via DSC

121.5 MHz

121.5 MHz

Features a low power homing signal to assist local and aerial rescue efforts

AIS

AIS

The live location of the man overboard is regularly updated and displayed via AIS

DUAL GNSS

Dual GNSS


Combines both GPS & Galileo GNSS receivers for accelerated detection

Class-M


Class-M

Compliant to European regulation ECC/DEC/ (22)02 relevant to the usage of MOB devices


PRODUCT FEATURES



WATER ACTIVATION
Device will automatically activate
when immersed in water for 2 seconds



STROBE LIGHT
High powered strobe light
to aid visual identification



COLOURED LEDs
LEDs change colour dependent
on status of beacon



ARMING DOOR
Swing door to prevent false
arming and activations



GNSS ZONE
Equipped with dual GNSS
for accurate location



WATER SENSOR
Weighted water sensor lead
ensures immersion in water



Audible Alarm
Highlight activation to both aid
location and raise awareness of
false activation



Water Sensor Lead
A weighted water sensor lead ensures
submersion in water so that the
device will automatically activate



Optional Recertification
Yearly servicing by an approved
sMRT service center ensures that
the product is ready for use



Test Functionality
Manual based testing provides
a status check on power and
functionality



Dual Activation Methods
Device can be activated manually or
after immersion in water meaning it
will still work if user is incapacitated



Environmentally Conscious
Packaged in 100% recyclable materials
& batteries only changed by an approved
service centre



Clipping System
Multiple fixing systems
allows easy attachment and
integration with life jackets



Dual GNSS Receivers
Integrated GPS and Galileo
receivers for accelerated
location detection



Water Proof
The device is designed to withstand
submersion up to 10 meters, ensuring
its protection against water damage

WHAT IS A Class-M MAN OVERBOARD DEVICE?

A Class-M MOB (Man Overboard) device is an AIS-enabled device designed to comply with ECC/DEC/(22)02 regulations. From December 31, 2024, only Class-M compliant MOB's and Mobile Aids to Navigation (AtoN) will be allowed to operate on AIS channels 1 and 2 in countries adopting the regulation, ensuring these channels are reserved for emergency use. Non-compliant devices will be restricted to channel 2006, which is not monitored for emergencies.

GENERAL

BATTERY TYPE	9V Lithium battery
MINIMUM ALERTING PERIOD	Minimum of 12 hours at -20°C.
BATTERY SHELF LIFE AT +20°C	5 years
OPERATING TEMPERATURE	-20° to +55°C (-4° to +131°F) as per IEC 60945:2002
STORAGE TEMPERATURE	-30° to +70°C (-22° to +158°F) as per IEC 60945:2002
DIMENSIONS	207mm (H) (including antenna) x 59mm (W) x 23mm (D)
WEIGHT	190g
ENVIRONMENTAL	EN 303 132 V2.1.1 IEC 60945:2002
STROBE LIGHT	30 candela, 170 degree dispersion, flash rate 12 /minute
ENVIRONMENTAL RATING	IP68 to 10 metres depth
MOUNTING OPTIONS	Designed to integrate with a SOLAS approved life jacket
SELF ID	ITU-R M.585-9 Compliant factory programmed freeform Maritime Identity with 972 prefix
COMPASS SAFE DISTANCE	0.5m (1.5ft)
ALERTING RADIUS	Typically 5NM

AIS/VHF TRANSMITTER PACKAGES

AIR BAND FREQUENCIES	121.500 MHz
ANTENNA TYPE	Vertically polarised
AIS Tx POWER OUTPUT	Nominal 1W EIRP
VHF TRANSMISSION FREQUENCIES	VHF DSC Channel 70: 156.525 MHz AIS Channel 1: 161.975 MHz AIS Channel 2: 162.025 MHz
VHF DSC Tx POWER OUTPUT	Nominal 1W EIRP
SIGNALLING TYPE	AIS and VHF-DSC

CONTROLS AND OPERATION

AUTOMATIC WATER ACTIVATION	After 2 seconds of water sensor immersion
MANUAL ACTIVATION	Once armed, press and hold the activate button

GPS RECEIVER

GNSS RECEIVER TYPE	GPS and Galileo
TTFF (TIME TO FIRST FIX)	25 seconds (typical) with nominal GPS signal levels -130dBm
GNSS UPDATE RATE	Every minute

VHF DSC AND AIS ALERTS

AIS	Within 30 seconds of GNSS position acquisition
INITIAL OPEN LOOP DSC ALERT	Within 30 seconds after activation
SUBSEQUENT OPEN LOOP DSC ALERTS	Every 5 minutes for the first 30 minutes, every 10 minutes thereafter until VHF-DSC acknowledgement received or the battery expires
FIRST DSC GPS DATA ALERT SENT	Immediately after GNSS position acquired

APPROVALS

RED ARTICLE 3.1 (A)	IEC 62368-1:2018 EN IEC 62368-1:2020+ A11:2020 CSA/UL 62368-1:2019 AS/NZS 62368-1:2022
RED ARTICLE 3.1 (B)	EN 301 843-8 Draft: V1.1.1_0.0.5 EN 301 843-1 Draft: V2.3.1_0.0.8 EN 60945:2022
RED ARTICLE 3.2	EN 303 132 V2.1.1 IEC 63269:2022 IEC 61108-1:2003 EN 302 152-1 V1.1.1 EN 303 098 V2.2.1
RED ARTICLE 3.3 (G)	RTCM 11901.2:2022

Pending FCC approvals, this product may not be sold or promoted in the United States